

Appendix A - Technical Specifications

Specifications

Length:	72" (183 cm).
Width:	32" (82 cm).
Running Area:	20" x 60" (51 cm x 152 cm).
Weight of Product:	320 lbs. (145 kg).
Shipping Weight	350 lbs. (159 kg).
Speed Range:	0.5 to 11.0 mph (0.8 to 17.6 kph) in 0.1 mph or 0.1 kph increments.
Incline Range:	0 to 15% grade.
Manual Mode:	Yes.
Programs:	Quick Start plus Manual, HR Control, Speed Interval 1, Speed Interval 2, Hill Interval, Pikes Peak, Rolling Hills, Hills, Weight Loss and Cardio.
Standard Features:	Safety Sentry™, Contact Heart Rate, Polar® wireless heart rate (chest strap not included), CSAFE, frame color choices include white texture, black texture, metaltone gold, black chrome and platinum sparkle.
Optional Features:	Unlimited custom colors available.
Power Requirement:	Grounded, dedicated circuit and one of the following: <ul style="list-style-type: none">• 115 VAC ±5, 60 Hz and 20 amps.• 220 VAC, 60 Hz 12 amps.• 230 VAC ±5, 50 Hz and 12 amps.
Motor:	3.0 hp, DC. continuous duty.
Emergency Stop:	Pull the emergency stop key (lanyard).
Maximum User Weight:	350 lbs. (158 kg).
Options:	Extension Handrails, Channel and volume controls on lower switch membrane for embedded A/V and Video mount bracket.

